

CCD-I86A/80M



Specifications:

| MODEL | CCD-I86A/80M |
|--------------------------|---------------------------------------|
| CHIPS | SONY |
| IMAGE SENSOR | 1/3" Super HAD CCD |
| ELECTRONIC PIXELS | PAL:500(H)*582(V) |
| SENSITIVE AREA | 4.9mm*3.7mm |
| LENS MOUNT | f=25mm/CS |
| ANGLE OF VIEW | 15° |
| M.O.D | 30CM |
| SYNC MODE | Internal |
| RESOLUTION | 480 TVL |
| MINIMUM ILLUMINATION | 0Lux (IR ON) |
| S/N | >=48dB |
| POWER SUPPLY | DC12V |
| GAMMA CORRECTION | 0.45 |
| GAIN CONTROL | AUTO |
| WHITE BALANCE | AUTO |
| ELECTRONIC SHUTTER | 1/60~1/100000secs; 1/50~1/100000secs. |
| VIDEO OUTPUT | 1.0 Vp-p Multi-video Signal 75Ω (BNC) |
| POWER CONSUMPTION | 200mA (IR OFF) ,800mA(IR ON) |
| IR LED | 84 Units Infrared LED(φ5mm/850nm) |
| IR ILLUMINATION | 3Lux |
| IR DISTANCE IN EFFECT | 80m |
| ENVIRONMENTAL RESISTANCE | IP66 |
| OPERATING TEMPERATURE | -20℃ ~ 50℃ |
| DIMENSION | 186*122*120mm |