

CCD-IA66A/110MR



Specifications:

MODEL	CCD-IA66A/110MR
CHIPS	SONY
IMAGE SENSOR	1/4" Super HAD CCD
ELECTRONIC PIXELS	PAL:752(H)*582(V)
SENSITIVE AREA	2.7mm*3.6mm
LENS MOUNT	22× (f=3.9mm~85.8mm)
MINI FOCAL DISTANCE	0.1m(WIDE ANGLE), 1.0m (NARROW)
SYNC MODE	Internal
RESOLUTION	480TVL
MINIMUM ILLUMINATION	0 Lux (IR ON)
S/N	>=52dB (AGC OFF)
DIGITAL ZOOM	270× Varifocal
POWER SUPPLY	DC12V
IRIS CONTROL	AUTO
VARIFOCAL	AUTO/MANUAL
WHITE BALANCE	AUTO
B.L.C	INTERNAL (ON/OFF)
VIDEO OUTPUT	1.0 Vp-p Multi-video Signal 75Ω (BNC)
POWER CONSUMPTION	200mA (IR OFF) ,950mA(IR ON)
COMMUNICATION CONTROL PORT	RS-485 Communication
IR LED	12 Units Infrared LED(φ10mm/850nm)
IR ILLUMINATION	3Lux
IR DISTANCE IN EFFECT	110m
ENVIRONMENTAL RESISTANCE	IP66
OPERATING TEMPERATURE	-20℃ ~50℃
DIMENSION	186*122*120mm