

VIDEO CONSOLE



Features:

- The DEINTERLACE can provide high quality picture, It can give sharp, stable image output to VGA.
- Compatible for Multi Signal inputs: Video, S-Video, PC (bypass).
- Input Video system 50-to-60HZ frame rate detection (NTSC/PAL(SECAM) for Video, S-Video).
- The DEINTERLACE output mode can be changed from 640*480, 800*600 to 1024*768. (60 Hz & 75Hz)
- No software driver required. It is applicable to all the O/S.
- Compact body and easy installation, no need to uncover PC case.
- No PC compatibility problem.
- Supports 3:2 pulldown conversion for film mode.
- Supports 2:2 pulldown graphic mode.
- 3 D Motion-adaptive interfiled de-interlacing.
- Supports function OSD (on screen display) control.
- OSD control menu : BRIGHTNESS, CONTRAST, COLOR, HUE, SHARPNESS, PICTURE MODE, RESOLUTION, FREQUENCY, RESET. PICTURE
- MODE : SPORT MODE, STATIC MODE.
- RESOLUTION : 640*480, 800*600 and 1024*768.
- FREQUENCY : 60 Hz and 75 Hz for each resolution.
- RESET : RESET to default setting.
- Panel button supports POWER, SOURCE, MENU, ENTER, UP & DOWN.
- Built-in microprocessor.

Specification:

- VGA input: RGB Input TYP.0.7Vpp
- VGA output: RGB output TYP.0.7Vpp
- Dimension: 12.5(L)x8(W)x3.3(H)cm

System Requirement:

- No specific PC system required.
- VESA compatible VGA monitor.
- Video input device (e.g.VCR, VCD, DVD, V8, LD player, TV game devices, etc.)

Hardware Connection and Application:

