

# WT-410N



## Features:

- Tiny size for discreet observation and portability
- Built-in microphone for audio monitoring
- 4 channels available to avoid possible interference
- Up to 100m(300ft) transmission range without block

## Specifications:

### Wireless Camera

Item	Unit	Value
Frequency	MHz	ISM 2,400~2,483 4CH*
Transmission Power	mW	10mW/CE; 2mW/FCC
Modulation Mode	※	FM
Bandwidth	MHz	18
Power Supply	VDC	8
Consumption Current	mA	50(Max)
Operating Temperature	°C/°F	-10 ~ +50 / +14 ~ +122
Storage Temperature	°C/°F	-40 ~ +85 / -40 ~ +185
Operating Humidity	RH	85%
Dimensions(W×L×H)	mm	39×35×33
Weight	g	25
Unobstructed Effective Range	m	100(Min)

### Receiver

Item	Unit	Value
Receiving Frequency	MHz	ISM 2,400~2,483
Intermediate Frequency	MHz	480

Frequency Stabilization	KHz	±100
Demodulation Mode	※	FM
Antenna	※	50ohm SMA
Local Leakage at Input Terminal	dBm	≤ -55
Receiving Sensitivity	dBm	≤ -85
Video Output	Vp-p	1Vp-p@75Ω, S/N>38dB
Audio Output	Vp-p	1Vp-p@600Ω
Power Supply	VDC	12
Power Consumption Current	mA	180
Operating Temperature	°C/°F	-10 ~ +50 / +14 ~ +122
Storage Temperature	°C/°F	-40 ~ +85 / -40 ~ +185
Operating Humidity	RH	85%
Dimensions [W x L x H ]	mm	92×78×23
Weight	g	200

\*Channel Frequency: CH1=2414MHz;CH2=2432MHz;CH3=2450MHz;CH4=2468MHz