

Indi-Lite

The Indi-Lite range of luminaires offers a cost effective method of providing efficient mains lighting from high lumen output T5 lamps enclosed in attractive but robust IP65 rated polycarbonate enclosures, resistant to moisture and dust. The polycarbonate lenses provide wide distribution with a degree of upward light.

The luminaires are supplied complete with stainless steel clips, removable gear tray, suspension brackets and two 20mm glands.

There is a choice between twin and single lamp variants. The luminaires are available as standard mains only or integral addressable emergency fittings. The luminaires can also be supplied with T8 lamps as an option.

All emergency versions provide 3-hour duration as standard, from integral high-temperature nickel cadmium batteries. The emergency versions can be used as part of the general lighting via a switched mains supply but they will automatically provide emergency lighting in the event of a complete loss of normal mains supply.

Installation

The luminaire is suitable for both surface and suspension mounting. The luminaires have two 20mm glands and suspension brackets

The luminaire fully complies with the requirements of EN60598.2.22 and supports all of the features of the LuxIntelligent emergency lighting test panels.



Features

- Polycarbonate base and defuser
- Electronic HF gear
- IP65 rated
- Stainless steel clips
- Slim attractive design

Specification

Supply voltage	230Volt (220-240V) @ 50Hz
Light source	Single and twin 28W/35W/49W T5 and 18W/36W/58W (T8)
Battery	Nickel cadmium 4Ahr
Recharge period	24 hours (14 hours for 1 hour duration)
Cable entry	Two 20mm gland entries
IP rating	IP65 at 25°C
Construction	Polycarbonate base and diffuser
Geartray	Removable white steel geartray

Order Codes and Options

IND128/AC:	Indi-Lite single 28W T5 mains-only luminaire
IND228/AC:	Indi-Lite double 28W T5 mains-only luminaire
IND128/M3/P:	Indi-Lite single 28W T5 3 hour maintained addressable luminaire
IND228/M3/P:	Indi-Lite double 28W T5 3 hour maintained addressable luminaire
IND258/AC:	Indi-Lite double 58W T8 mains-only luminaire
IND258/M3/P:	Indi-Lite double 58W T8 3 hour maintained addressable luminaire