

ActiV Conventional Hi-Output 100dB(A) Wall Sounder (deep base)

Part No. **BF430C/CC/DR**



Overview

LPCB certified to EN54-3 (Sounders).

Impressive 100dB(A) sound output @ 1m.

31 selectable primary and secondary tone pairs and two volume levels (high and low)

Alarm Current at 30Vdc = 5.5mA.

Alarm Current at 18Vdc = 3.8mA.

IP33C rated.

Manufactured in the UK by C-TEC.

Technical Specifications

Approvals/certifications	Certified to EN54-3 by the LPCB.
Protocol/compatibility	Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use)
Application/operation	Designed to be wall mounted. Can be used in covered outdoor areas.
VAD category & coverage	N/A
Flash rate & colour	N/A
Supply/operating voltage	18 to 30V DC.
Nominal SPL (Sound Pressure Level)	100dB(A).
Alarm current	At 30Vdc: 5.5mA; At 18Vdc: 3.8mA.
Product dimensions (mm)	114mm diameter x 132mm deep.
IP Rating	IP33C (Type B).
Weight	315g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).